

Listing of Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

1. (Original) A seal comprising a generally annular body for location between two members to be connected, the body comprising a deformable lip for abutting one of the members to be connected, the lip being arranged such that the lip rolls radially when subject to axial compression.
2. (Original) The seal of claim 1, wherein the body is generally tapered, with an upper portion being of greater diameter than a lower portion.
3. (Original) The seal of claim 1, wherein the body is generally frustoconical.
4. (Canceled)
5. (Original) The seal of claim 1, wherein the lip provides a generally cylindrical surface profile.
6. (Original) The seal of claim 5, wherein the surface profile of the lip is substantially hemicylindrical.

7. (Original) The seal of claim 5, wherein a highest point of the lip is positioned radially outwardly of a mid-point of the adjacent body wall.
8. (Original) The seal of claim 1, wherein the lip in use abuts only one of the members to be connected.
9. (Currently Amended) The seal of claim 1, wherein the body further comprises a [[flange
]]shoulder located spaced from the lip, for spacing the lip from the second member to be connected.
10. (Canceled)
11. (Original) The seal of claim 1, wherein the body is substantially resilient.
12. (Original) The seal of claim 1, wherein the body comprises elastomeric material.
13. (Original) The seal of claim 1, wherein the lip further comprises friction-increasing formations thereon.
14. (Original) The seal of claim 1, wherein the lip further comprises ridges thereon.

15. (Original) The seal of claim 14, wherein the ridges extend substantially circumferentially around the lip.
16. (Original) The seal of claim 1, wherein the body further comprises a sealing portion for forming a seal between the body and the second member to be connected.
17. (Original) The seal of claim 16, wherein the sealing portion comprises a protrusion on an outer surface of a body wall.
18. (Original) The seal of claim 1, further comprising an interior sealing member.
19. (Original) The seal of claim 18, wherein the interior sealing member comprises a diaphragm extending radially within the body.
20. (Original) The seal of claim 18, wherein the interior sealing member is adapted to be deformed when subject to force exerted by a member to be connected.
21. (Canceled)

22. (Canceled)

23. (New) A seal comprising a generally annular body for location between two members to be connected, the body comprising a deformable lip for abutting one of the members to be connected, the lip defining a circumferential edge and being arranged such that the lip edge rolls radially when subject to axial compression.